



# WIGGIN PRECAST CORPORATION

P.O. BOX 1138 POCASSET, MASSACHUSETTS 02559  
 TEL: 508.564.6776 FAX: 508.564.6770

## SELECTING THE RIGHT BULKHEAD SIZE

### JOB REQUIREMENTS:

- 1.) FOUNDATION WALL OPENING IS 40" WIDE MAX. ALL SIZES  
NO BLOCK FOUNDATIONS
- 2.) ADEQUATE ACCESS FOR DELIVERY TRUCK (SOLID GROUND CONDITIONS)  
8' WIDE TRUCK NEEDS TO DEPLOY STABILIZERS 8' TO EACH SIDE  
TRUCK CAN REACH UP TO 25' TO INSTALL
- 3.) STAIRWELL SHOULD BE 2" TO 6" ABOVE FINISHED GRADE.
- 4.) DOORS WILL NOT BE INSTALLED UNLESS VERTICAL WALL IS IN PLACE  
WALL MUST BE CLEAR OF SIDING AROUND BILCO DOOR AREA.

TYPE	A	B	C	D	OUTSIDE WIDTH DIMENSION
O	60"	30"	60"	---	51.5"
B	68"	22"	66"	---	55.5"
C	76"	19.5"	74"	---	55.5"
D	84"	22"	86"	12"	55.5"

